

Payload SDK

Development Kit

开发套件

User Guide

使用说明

V1.0 2018.03



Contents

EN	Disclaimer	2
	Warning	3
	Product Profile	4
	Usage	7
CHS	免责声明	10
	产品使用注意事项	10
	产品简介	11
	使 用	14

Disclaimer

Congratulations on purchasing your new DJI™ product. The information in this document affects your safety and your legal rights and responsibilities. Read this entire document carefully to ensure proper configuration before use. Failure to read and follow instructions and warnings in this document may result in serious injury to yourself or others, damage to your DJI product, or damage to other objects in the vicinity. This document and all other collateral documents are subject to change at the sole discretion of DJI.

By using this product, you hereby signify that you have read this disclaimer and warning carefully and that you understand and agree to abide by the terms and conditions herein. You agree that you are solely responsible for your own conduct while using this product, and for any consequences thereof. You agree to use this product only for purposes that are proper and in accordance with all applicable laws, rules, and regulations, and all terms, precautions, practices, policies and guidelines DJI has made and may make available.

DJI accepts no liability for damage, injury or any legal responsibility incurred directly or indirectly from the use of this product. The user shall observe safe and lawful practices including, but not limited to, those set forth in this document. Notwithstanding above, your statutory rights under applicable national legislation are not affected by this disclaimer.

DJI is a trademark of SZ DJI TECHNOLOGY CO., LTD. (abbreviated as "DJI") and its affiliated companies. Names of products, brands, etc., appearing in this document are trademarks or registered trademarks of their respective owner companies. This product and document are copyrighted by DJI with all rights reserved. No part of this product or document shall be reproduced in any form without prior written consent of or authorization from DJI.

Warning

1. Go to <https://developer.dji.com/payload-sdk/> and download the relevant manuals before use. Read and understand the manuals, and then strictly follow the instructions in the manuals when using the Payload SDK Development Kit.
2. Connect the cables correctly by following the instructions in this *Payload SDK Development Kit User Guide* otherwise the connectors may get burned and the Payload SDK Development Board may get seriously damaged.
3. Make sure there are no short-circuits and all the cables are in good condition. DO NOT use cables that have been damaged in any way.
4. Be sure to use the product in strict accordance with the Specifications (including those for voltage, current, and temperature) listed in this document. Failure to do so may reduce the product service life or even lead to permanent damage.
5. Take measures to protect the Payload SDK Development Board from static electricity and physical damage.
6. Always keep the Payload SDK Development Board clean otherwise a short-circuit may occur and the Payload SDK Development Board's performance may be negatively affected.
7. DO NOT use your hand to touch the chips on the Payload SDK Development Board as doing so may damage the Payload SDK Development Board and its performance may be negatively affected due to static electricity.
8. If you detect any flames, smoke, strange smells, or other abnormality disconnect the Payload SDK Development Board from the power source immediately.

Product Profile

Introduction

The Payload SDK is designed to enable third-party payload developers and manufacturers to use the DJI flight platform with their own specialized payloads. The Payload SDK provides programming access to DJI flight platform resources including power systems, communication links, and aircraft status parameters such as GPS data, flight attitude data, and app date/time. The Payload SDK can be used in conjunction with other DJI software such as the Mobile SDK, the DJI Pilot app, and the DJI ASSISTANT™ 2 desktop application.

Compatible Flight Platforms

MATRICE™ 200, Matrice 210, and Matrice 210 RTK.

Intended Users

Customized payload development companies.
Research institutions.

In the Box


DJI SKYPORT Adapter ×1



Payload SDK Development Board ×1



Round Ribbon Cable
250 mm* ×1



Flat Ribbon Cable 30 mm*
x1



Ribbon Cable Connector*
x3




* Accessories are not
cover under warranty.

Overview

DJI SKYPORT Adapter

Dimensions




Interfaces

Interface Type	Parameters	Remarks
Power supply	12 V / 4 A	Maximum working current is 4 A.
Command communication	UART TTL (3.3 V), CAN	Used to communicate with the SKYPORT adapter.

Data transfer MDI Ethernet Port

Used to transmit the code streams and user-defined downlink data.

Payload SDK Development Board



Ports

Port Code	Port Name	Remarks
J5	SKYPORT Connector	Connect to the SKYPORT adapter using the Round Ribbon Cable 250 mm.

J7	External Test Port	Transfers the UART/CAN signal from the SKYPORT adapter into a pinned connector to facilitate connection to other platforms.
J10	Ethernet Port	Used to transmit the code streams and downlink data.
J11	MCU Debug Port	Debug programs and download microcontroller programs with a debugger via this port.
J12	USB Debug Port	Print log files and update firmware using a PC connected to this port.

Usage

Feature Overview


Features	Description
Direct data transmission	Transmit data directly between the Mobile SDK and SKYPORT adapter via a UART/CAN port.
Ethernet port features	UDP protocol is used when transmitting a large quantity of downlink data via the Ethernet port. Mobile SDK provides stream analysis when transmitting code streams in the specified format.
Data push	Push aircraft data to the payload including GPS data, flight attitude data, and app date/time.

Gimbal and camera interface support	The Payload SDK provides a standard camera and gimbal payload interface to enable rapid development.
DJI Assistant 2 compatibility	DJI Assistant 2 provides SKYPORT adapter binding and unbinding and parameter configuration functionality.
Mobile SDK compatibility	The Mobile SDK provides related interface functionality.
DJI Pilot compatibility	DJI Pilot provides custom control options and support for third-party camera/gimbal payloads.


Installation and Connection

Follow the steps below to install and connect the Payload SDK.


1. Use the Round Ribbon Cable 250 mm to connect the SKYPORT adapter to the Payload SDK Development Board.



2. Attach the SKYPORT adapter to the aircraft's gimbal connector.



Align the white and red dots and insert the SKYPORT adapter.



Rotate the SKYPORT adapter to the locked position.

Learn More

Go to <https://developer.dji.com/payload-sdk/> and download the relevant manuals before use. Read and understand the manuals, and then strictly follow the instructions in the manuals when using the Payload SDK Development Kit.

免责声明

感谢您购买 DJI™ 产品。本文所提及的内容关系到您的安全以及合法权益与责任。使用本产品之前，请仔细阅读本文以确保已对产品进行正确的设置。不遵循和不按照本文的说明与警告来操作可能会给您和周围的人带来伤害，损坏本产品或其它周围的物品。本文档及本产品所有相关的文档最终解释权归大疆™ 创新（DJI）所有。如有更新，恕不另行通知。请访问 www.dji.com 官方网站以获取最新的产品信息。

一旦使用本产品，即视为您已经仔细阅读免责声明与警告，理解、认可和接受本声明全部条款和内容。您承诺对使用本产品以及可能带来的后果负全部责任。您承诺仅出于正当目的使用本产品，并且同意本条款以及大疆创新（DJI）制定的任何相关条例、政策和指引。

大疆创新（DJI）对于直接或间接使用本产品而造成的损坏、伤害以及任何法律责任不予负责。

用户应遵循包括但不限于本文提及的所有安全指引。

即使存在上述规定，消费者权益依然受当地法律法规所保障，并不受本免责声明影响。

DJI 是深圳市大疆创新科技有限公司及其关联公司的商标。本文出现的产品名称、品牌等，均为其所属公司的商标或注册商标。本产品及手册为大疆创新版权所有。未经许可，不得以任何形式复制翻印。

产品使用注意事项

1. 使用前，请前往 <https://developer.dji.com/payload-sdk/> 获取详细的使用说明，仔细阅读里面的注意事项并了解具体使用方法，然后再使用该产品。
2. 请按照说明书正确连接线材，以免烧坏接口以及 Payload SDK 开发板。

3. 使用前请检查线材有无老化、短路。老化或短路的线材不适合继续使用。
4. 请按照本文规定的工作环境（如电压、电流、温度等参数）使用，否则将会影响产品寿命或造成永久性损坏。
5. 安装时注意做好保护，防止静电、物理损坏。
6. 请保持 Payload SDK 开发板的干净整洁，避免由于异物造成短路或性能下降。
7. 请不要用手直接接触 Payload SDK 开发板上的芯片，避免由于静电放电造成开发板损坏或性能下降。
8. Payload SDK 开发板上电后如发现火花、冒烟、焦糊味或其它异常，请立即关掉电源。

产品简介

概述

Payload SDK (PSDK) 主要用于让第三方厂家基于 DJI 飞行平台进行负载设备开发。第三方厂家可以使用飞行平台的资源，如电源、通讯链路、状态信息（GPS 信息、姿态信息、时间日期）等。同时，Payload SDK 将提供配套的软件支持，如 Payload SDK, Mobile SDK, DJI Pilot, DJI ASSISTANT™ 2 等。

适配机型

MATRICE™ 200, Matrice 210, Matrice 210 RTK

面向用户


二次开发定制化开发负载的公司。
科研院校。

物品清单


DJI SKYPORT 连接器 × 1



Payload SDK 开发板 × 1



同轴线 250mm* × 1



同轴线 30mm* × 1



同轴线端座 * × 3




* 物品均不在保修范围
以内。

部件说明

DJI SKYPORT 连接器

尺寸




单位: mm

接口参数

接口类型	参数	说明
供电电源	12V/4A	工作峰值电流最大为 4A。
指令通信方式	UART TTL(3.3V)、CAN	用于和 SKYPORT 连接器进行指令通讯。
大数据传输	MDI 网口	可以通过网口传输码流以及用户自定义的下行数据。

Payload SDK 开发板



接口说明

接口编号	接口名称	接口说明
J5	SKYPORT	可通过同轴线连接 SKYPORT 连接器。
J7	对外测试接口	将连接 SKYPORT 接口的 UART/CAN 转成排针形式，方便用户连接通讯接口到自己的负载平台中。
J10	网口	可通过该网口传输码流和下行数据。
J11	MCU 调试接口	MCU 调试接口，可以通过调试器调试和下载单片机程序。
J12	USB 调试口	USB 调试接口，接入 PC 后可打印 LOG 以及升级固件。

使 用

功能概览


功能	说明
数据透传	通过 SKYPORT 的 UART/CAN 接口可与 Mobile SDK 透传数据。
网口功能	通过网口采用 UDP 协议透传大量下行数据。当传输指定格式的码流时，Mobile SDK 提供码流解析功能。
状态推送	推送 UAV 状态数据供负载使用，包括 GPS 信息、姿态信息、APP 时间等。
相机云台类负载接口支持	当负载为相机云台类负载时，Payload SDK 定义了一套标准的相机云台类负载接口，方便用户快速开发。
DJI Assistant 2 支持	DJI Assistant 2 提供了 SKYPORT 连接器绑定、解绑以及参数配置功能。

Mobile SDK 支持	Mobile SDK 提供与 Payload SDK 配套的接口支持
DJI Pilot 支持	DJI Pilot 提供自定义控件功能并可支持第三方开发的相机云台类负载


安装连线

请根据以下步骤进行安装。


1. 使用同轴线连接 SKYPORT 连接器和开发板。



2. 安装 SKYPORT 连接器到飞行器的云台接口。



对齐 SKYPORT 连接器上的白点与飞行器云台接口红点，并嵌入安装位置。



旋转 SKYPORT 连接器至锁定位置（红点对齐），以固定 SKYPORT 连接器。

更多使用

请至网页 <https://developer.dji.com/payload-sdk/> 获取详细的使用说明和更多研发支持。

DJI Support
DJI 技术支持

<http://www.dji.com/support>

If you have any questions about this document, please
contact DJI by sending a message to **DocSupport@dji.com**.

如果您对说明书有任何疑问或建议，请通过以下
电子邮箱联系我们：**DocSupport@dji.com**。

Printed in China.

中国印制

YC.BZ.SS000386.01