



czi WeChat  
Account



czi WeChat  
Channel



Note: Products do not  
include drones



Police



Search&Rescue



Maritime

# MP130 V2

## Digital Voice Broadcasting System

130dB powerful volume  
500m ultra-loud sound



GUANGZHOU CHENGZHI INTELLIGENT MACHINERY TECHNOLOGY CO., LTD.



<http://www.gzczzn.com>



No. 5, Longlin Street Center, Yinhu Creative Park,  
No.1 Guangshan Road, Tianhe District,  
Guangzhou City, China



## Digital Voice Broadcasting System MP130 V2



Product  
Details

The MP130 V2 is a Long-Range Acoustic Device(LRAD) for UAVs, with ultra-high sound pressure to clearly transmit voice to distant locations, with an effective range of up to 500 meters. With the second generation of the UAV digital voice broadcasting system, it combines DJI PSDK links to ensure voice broadcasting anytime and anywhere. Broadcasting more clearly.

The MP130 V2 has strong sound penetration, is small, lightweight has low power consumption, and has excellent magnetic shielding performance, developed for UAV industry applications. With the DJI Skyport V2.0 interface, it is seamlessly compatible with DJI Matrix M200 V2/M300 series flight platforms.

### Product Advantages

**130**  
dB

Maximum  
volume

**500**  
m

Effective  
loudspeaker distance

**PSDK**

Communication  
link



Cell phone  
audio files

#### Live broadcasting & Various modes

- TTS、voice upload
- Upload and playback audio file
- Call to czi voice library text library etc.

#### 130dB 500meters

- 130dB powerful volume
- 500m ultra-loud sound

#### Synchronous pitching & Precise broadcasting

- Instantly available via DJI
- Automatic synchronous pitching
- Follow the gimbal camera to optimum broadcast results

Warm Tips: The final interpretation of this material belongs to Guangzhou Chengzhi Intelligent Machinery Technology Co.,Ltd. Products are subject to change without notice, please refer to the company official website or the latest information.

### Technical Parameters

Model	MP130 V2
Dimensions	140*140*125mm
Weight	550±5g
Power	25W
Maximum sound pressure	130dB
Effective broadcast distance	500m
Directional	80°x50°(horizontal x vertical)
Operating temperature	-20°C~+40°C
Mounted interface	DJI Skyport V2.0 (Suitable for DJI M300 RTK) czi quick release adapter ring (suitable for other brands of UAV)
Communication link	DJI PSDK link
Pitch angle	0-90° (UAV M200 V2) 0-60° (UAV M300)
Broadcasting method	-Live broadcasting -Upload a recording -Play audio files -Background music (automatic dodging) -Text to speech (supports many dialects)
Audio formats	mp3/wav/m4a/flac/aac
Operation System	Android 5.0 and above